

Wall Indoor units

# AERI | AEVI | AEMI



- Ionizer
- Anti-corrosion protection - gold coating
- Heating at temp. of -20°C
- 3D DC Inverter
- Wi-Fi ready
- Mono and multi compatibility

- Operating range up to -20°C
- Heating
- Cooling
- 3D air flow
- Wi-Fi ready
- Mono and multi compatibility

- Biofilter
- Anti-corrosion protection - gold coating
- 3D DC Inverter
- I Feel function
- Automatic operating mode
- Wi-Fi ready

	Model	ACP-07CH21AEMI/I	ACP-09CH25AERI/I+ R32	ACP-12CH35AERI/I+ R32	ACP-18CH50AERI/I+ R32	ACP-12CH35AEVI/I2s R32
<b>Indoor unit</b>	Capacity (W)	2052	2638	3517	5275	3517
	Capacity (W)	2346	2931	3810	5568	3810
	Air flow (m³/h) - HI / MID / LOW	520 / 460 / 340	483 / 362 / 303	584 / 477 / 395	730 / 500 / 420	558 / 478 / 384
	Coolant	R32	R32	R32	R32	R32
	Dehumidifying capacity (L/h)	1.0	1.0	1.2	1.8	1.2
	Noise - Sound Pressure (dB(A)) - HI / MID / LOW / SI	40 / 30 / 26 / 21	42 / 35 / 25 / 21.5	42 / 35 / 25 / 22	43 / 38 / 33.5 / 28	37.5 / 32 / 30 / 24
	Volume under standard conditions (dB)	≤ 54	≤ 56	≤ 56	≤ 57	≤ 51
	Packaging dimensions (mm)	870 x 270 x 360	875 x 285 x 375	875 x 285 x 375	1045 x 305 x 410	985 x 385 x 265
	Device dimensions (mm)	805 x 194 x 285	802 x 189 x 297	802 x 189 x 297	965 x 215 x 319	897 x 312 x 182
Gross / net weight (kg)	9.7 / 7.5	11.1 / 8.6	11.1 / 8.6	14.2 / 10.9	14.2 / 10.5	
<b>Connections</b>	Liquid phase pipe diameter	1/4"	1/4"	1/4"	1/4"	1/4"
	Gas phase pipe diameter	3/8"	3/8"	3/8"	1/2"	3/8"
<b>Interconnect cable</b>	Outdoor unit power supply (mm²)	4 x 1.0	4 x 1.0	4 x 1.0	4 x 1.0	5 x 1.5
	Power Supply	~220-240V/1/50Hz; Outdoor unit				